

BATTERY BOOSTER CABLE SETS

 <p>LMBC100-25060072B 100A 1. CABLE: SIZE: 0.25MMX60XOD7.2MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 135MM</p>	 <p>LMBC200-25080075B 200A 1. CABLE: SIZE: 0.25MMX80XOD7.5MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 140MM</p>	 <p>LMBC200-25081095B 200A 1. CABLE: SIZE: 0.25MMX81XOD9.5MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 135MM</p>
 <p>LMBC300-25100080B 300A 1. CABLE: SIZE: 0.25MMX100XOD8.0MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 140MM</p>	 <p>LMBC400-25120090B 400A 1. CABLE: SIZE: 0.25MMX120XOD9.0MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 145MM</p>	 <p>LMBC500-30110100B 500A 1. CABLE: SIZE: 0.30MMX110XOD10.0MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 180MM</p>
 <p>LMBC500-32311120F 500A 1. CABLE: SIZE: 0.32MMX311XOD12.0MMX5M 2. CLAMP: MATERIAL: IRON WITH ZINC PLATED LENGTH: 160MM</p>	 <p>LMBC500-40128110B 500A 1. CABLE: SIZE: 0.40MMX128XOD11.0MMX2.5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 165MM</p>	 <p>LMBC600-30120100B 600A 1. CABLE: SIZE: 0.30MMX120XOD10.0MMX2.5M 2. CLAMP: MATERIAL: IRON WITH PE COATED LENGTH: 175MM</p>
 <p>LMBC800-30170110C 800A 1. CABLE: SIZE: 0.30MMX170XOD11.0MMX3.0M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 150MM</p>	 <p>LMBC800-32435130F 800A 1. CABLE: SIZE: 0.32MMX435XOD13.0MMX5M 2. CLAMP: MATERIAL: IRON WITH COPPER PLATED LENGTH: 160MM</p>	 <p>LMBC1000-30226120C 1000A 1. CABLE: SIZE: 0.30MMX226XOD12.0MMX3.0M 2. CLAMP: MATERIAL: IRON WITH NICKEL PLATED LENGTH: 150MM</p>

- CONDUCTOR MATERIAL: COPPER CLAD ALUMINUM WIRE
- CABLE LENGTH: A=2.0M, B=2.5M, C=3.0M, D=4.0M, F=5.0M
- IF YOUR REQUIRED CABLE SIZE IS NOT COVERED BY OUR LIST, PLEASE GIVE US YOUR DETAILS, SUCH AS FOLLOWING:

LMBC1000 - 0.30MM X 226 X OD12.0MM X 3.0M
CLAMP AMP DIAMETER OF CONDUCTOR OUTSIDE DIAMETER CABLE
EACH STRAND STRANDS OF CABLE LENGTH